

Selection Guide for CNC Rotary Tables ...



pl




10/2018 | EN

... for ME- and M-One-series

Applications

CNC rotary tables for economical manufacturing:
pL LEHMANN has suitable and rational solutions for
nearly every industry




pL rotary tables in use: on over **40** different machine brands
and over **160** different machine models.

pL competence: Integration in **all known** CNC control systems
(Fanuc, Siemens, Heidenhain, Haas, Winmax, Mitsubishi, Brother,
Mazatrol, Okuma ...), for new machines as well as for retrofits

Organization

Professional products from professional partners:
Maple and pL LEHMANN provide
first-class service to common customers



Overview and Facts

Up to **210 rpm**
up to **0.21 sec / 90°**

NEW
up to +30 %

High speed

Extended travel in
Z- and X-direction

More space

High spindle load,
heavy-duty bearing

Heavy duty

E-Series



**Rotary tables suitable for
simultaneous operation!**

Save energy



Benefits of PGD by pL LEHMANN as compared to Direct Drive: small servo, low power draw, no cooling system, and a significantly reduced energy consumption when machining with unclamped rotary table.

Energy label at the left

An intuitive rating as consumption greatly depends on usage, and without any liability assumed, following the directives on energy labelling

**See main catalog
for more features**

High torque

Feed torque up to
850 Nm (provisional)

Adaptability

Multifunctional
spindle HSK

Precision

On the workpiece, as
precise as **2 µm / 100 mm**

NEW
up to +30 %

Overview and Facts

Pneum. clamping
up to **7,000 Nm**

High clamp

NEW
up to +150 %

Large parts
up to **ø 500**

Big size

PGD backlash-free
long-life gear unit

No backlash

T-Series



**All base plates
made of steel**

NEW

with integrated hole pattern for
slot spacing of 100 and 125 mm,
integrated alignment system
lineFIX for lengthwise or cross-
wise clamping.

M-Series



NEW

Connectivity

Wireless monitoring,
for operation & service

No adjust

Load change without
parameter adjustment

Less cost

No cooling system,
no hydraulics

Machine Overview



ME-655



M-One 6



M-One 6 APC



M-One 80


A word from Maple:

«Where quality comes standard – 25 Years of Endless Innovation

With countless years of past experience for improving and join new technology; we are able to promote better efficiency products, and achieve better results and large lasting accuracy. In last then 3 years, we have sold many hundreds units of CNC products to the world.

MAPLE appreciates all our customers support and will strive to prove our customers better products and more ways to help you find the Maple machine that best fits your needs.»

The right machine/rotary table combination for economical production: this Selection Guide helps you make the right selection


[illegible]

** The recommended rotary tables do not exceed 50 % of the allowed table load.


	EA-507 X2	EA-510 X2	EA-520 X2	EA-530 X2
M-One 6 APC	433	417		

<https://www.lehmann-rotary-tables.com/website/static/lib/pdfjs/viewer/selection-guide-maple-10.2018-en-dok-0349-0.pdf&zoom=page-fit>

For further details about the rotary tables, see p. 12 and higher or refer to the main catalog



Rotary table installation with pL clamping claws in accordance with the operating manual



<https://www.lehmann-rotary-tables.com/website/static/lib/pdfjs/viewer/selection-guide-maple-10.2018-en-dok-0349-0.pdf&zoom=page-fit> Page 8 of 21

Explanations for pp. 8 to 11


[illegible]

A diagram of a rectangular area. The total width is labeled X and the total height is labeled Y . A green rectangular region is shown with width X_2 and height Y_1 . A white rectangular region is shown with width X_1 and height Y_2 . The green region is to the left of the white region, and the white region is at the bottom of the green region.

[illegible]

Page 9 of 21

X-mounting



Rotary table installation using hole pattern in base plate



TIP1




TAP1



TOP1.2

[illegible][illegible]

Overview of E-Series




Overview of E-Series

News in brief

1. High speed up to **210 rpm**
2. Feed torque up to **850 Nm** (tentative)
3. Steel base plates with hole pattern (suitable for slot spacing of 100 and 125 mm)
4. Cycle time **90°** as fast as **0.21 sec.**



Weight data represent the standard load; higher weights possible, but require modification of rotational speed, acceleration and jerk limitation.




50x	507 (standard) or 508 (high speed)
51x	510 (standard) or 511 (high speed)
EA	single-axis, single-spindle CNC rotary table
rotoFIX	modular clamping yoke system
longFI FX	modular shaft clamping system

Overview of T-Series




More space for
workpiece and fixtures



Overview of T-Series

News in brief


1. Up to **150 %** higher clamping torque in tilting axis
2. Fewer variant – more solution
3. Larger workpiece $\varnothing$ possible
4. Spatially optimized arrangement of the dividing axis



Weight data represent the standard load; higher weights possible, but require modification of rotational speed, acceleration and jerk limitation.

50x510	508510 (standard) or 508510 (high speed)
51x520	510520 (standard) or 511520 (high speed)
TIPc	Two-axis rotary table, no counter bearing, compact
TAPc	Two-axis rotary table, with supporting bearing, compact
TAP	Two-axis rotary table, with supporting bearing
TOP	Two-axis rotary table, with clamped counter bearing
TGR	Two-axis rotary table, with clamped counter bearing, specifically for grinding applications


Overview of M-Series



Overview of M-Series

News in brief

1. Up to **54 %** higher clamping torque in tilting axis
2. Fewer variant – more solution
3. Spindle distance min. **130 mm**
4. Spatially optimized arrangement of the dividing axis



50x 507 (standard) or 508 (high speed)

51x 510 (standard) or 511 (high speed)

M2 Single-axis, multi-spindle rotary table, 2-position

M3 Single-axis, multi-spindle rotary table, 3-position

T2 Two-axis multi-spindle rotary table, 2-position

T3 Two-axis multi-spindle rotary table, 3-position

Spindle System Accessories

Extremely wide assortment for workpiece clamping.
Standardized interface in front and rear: maximum universality

Spindle accessories in rear

- + Rotary unions **up to 250 bar**
- + Clamping cylinder **23 kN at 120 bar**
- + Angular position measuring systems **as precise as ± 1 arcsec**



Spindle accessories in front



Tailstock and counter bearing



ripas zero point clamping system



FA-507 with ripas auto and ripas adapter

CAPTO clamping (on request)




FA-507 with CAPTO retrofit kit

Sales and Service

Present in over 20 countries: from sales consultation to the final service




Services from A to Z



Increase productivity – Extend lifecycle

Comprehensive and professional services throughout the product life cycle – maximum availability with consistent quality and high productivity.



For more information please see www.lehmann-rotary-tables.com



ROTARY TABLES · PRECISION TECHNOLOGY · SOFTWARE

Headquarters

PETER LEHMANN AG
CH-3552 Bärau
Phone +41 (0)34 409 66 66
Fax +41 (0)34 409 66 00
pls@plehmann.com
www.lehmann-rotary-tables.com

Representatives / Agencies

Europe

- Austria
- Benelux
- Czech Republic (vacant)
- Finland
- France
- Germany
- Hungary (vacant)
- Italy
- Norway
- Poland
- Portugal
- Russia
- Slovenia
- Spain
- Sweden
- Turkey
- UK

America

- Brazil
- Canada
- Mexico
- USA

Asia

- China
- India
- Japan
- Malaysia
- Singapore
- South Korea
- Taiwan
- Thailand
- Vietnam

Africa

- South Africa



● Headquarters
 ● direct sales partner
 ● pL Solutions® partner
 ● value added reseller & partner
 More information (address, telephone number...) at www.lehmann-rotary-tables.com

Subject to change / Edition: 10/2018